



PAMATKOMPLEKTĀCIJA		Merv. / kods	Panther 56	Panther 72	E 80	E 120	Viscomat 70	Viscomat 90	P 80 EEX M	ByPass3000		Bipump DC		Panther DC	
Tehniskie parametri	Elektropieslēgums (spriegums)	v	230	230	230	230	230	230	230	12	24/12	12	24	12	24/12
	Plūsmas ātrums	l/min	<56	<72	<75	<100	<25	<50	<75	<50	<50/30	<85	<56	<70/35	
	Sūkņa jauda	w	370	450	500	750	750	1600	750						
	Sūkņa apgriezieni minūtē	apgr/m	2800	2800	1400	1400	1450	1450	1400	2900	2900/1500	2000	2900	3500/1800	
	Sūkņa ieplūdes/izplūdes savienojuma izmērs	collas	1"	1"	1"	1"	1"	1"	1"	3/4"		1"	1"		
	Sūkņa trokšņu līmenis	dB	<70	<70	<70	<70	<70	<70	<70	<70	<70	<70	<70	<70	
	Sūkņa darbības cikls	min	∞	∞	∞	∞	∞	∞	∞	∞	30	30	30	30	
	Apvadventīlis (By Pass)		x	x	x	x	x		x	x		x		x	
	Filtrs degvielas sūknī (nerusejoša terauda siets)		x	x										x	
	Atloka savienojums			x	x	x			x			x			
	Ieslēgšanas / izslēgšanas slēdzis		x	x	x	x	x	x				x		x	
	Šķidrums, kurus drīkst pārsūknēt (Dizeļdegviela, Eļļa, Rapšu eļļa)		D	D	D	D	D,E,R	D,E,R	D	D	D	D	D	D	
	Aizsardzības klase IP		IP55	IP55	IP55	IP55	IP55	IP55	IP55	IP55	IP55	IP55	IP55	IP55	
	Iepakojuma izmēri	mm	195x355x270	195x355x270	195x355x270	195x355x270	350x200x280	350x200x280	650x290x300	200x350x270	190x350x280	195x355x270	195x355x270	195x355x270	
	Svars	kg	7.4	7.9	13	15.6	14.1	14.1	26.5	3.5	9.9	7.5	123.45	162.48	
Cena ar PVN 21%:			118.00	144.88	211.60	283.07	226.83	259.16	485.14	90.48	235.66	123.45	162.48		